

ROWAC MIG-200 Pulse

MIG DC Inverter



Standard



Earth clamp

Electrode holder

MIG torch

Optional



5m gas tube

Gas-pressure meter

LIFT TIG

flux cored wire

GB MIG DC Inverter

- MIG, Pulse, Double pulse, MMA & LIFT TIG function
- VRD function built in
- Light weight design make it easy to be carried
- Adopt advanced single IGBT technology, increased reliability
- Complete accessories-electrode holder, earth clamp with cable, MIG torch
- 2T/4T mode
- Arc force, hot start and anti-stick built in

NL MIG DC Inverter

- MIG, Pulse, Dubbel pulse, MMA, Lift-TIG functie
- VRD ingebouwd
- Makkelijk te transporteren vanwege licht gewicht
- Geavanceerde IGBT technologie, hoge betrouwbaarheid
- Compleet geleverd met: elektrode kabel, MIG pistool en werkstukkabel
- 2takt/ 4 takt
- Ingebouwde Arc force, hotstart en anti-stick

D MIG DC Inverter

- MIG, Pulse, Doppel Pulse, E-Hand- und WIG-Liftarc-Schweißen
- VRD eingebaut
- Sehr leicht - Gehäuse aus Aluminium und schlagfestem Kunststoff
- IGBT Technik,
- Komplett geliefert mit: Elektrodenhalter, Massekabel und MIG Brenner
- 2 Takt/ 4 Takt
- Arc Force, Hotstart und Anti Stick

ROWAC MIG-200 Pulse MIG DC Inverter



Model	Model	Model	RÖWAC MIG-200 Pulse		
Power supply voltage	Netspanning	Netzspannung	230 ± 10%		
Rate input capacity	Vermogen	Anschlussleistung	7.8	6	7.5
Frequency (inverter)	Net frequentie	Netzfrequenz	50		
Rated input current	Max. primaire stroom	Max. Stromaufnahme	35/20	26/13	33/25
Output current range	Max. lasstroom	Max. Schweißstrom	50-200	10-300	10-160
Function	Functie	Function	MIG	TIG	MMA
Duty cycle (40°C - 10 min)	Inschakelduur (40°C - 10 min)	Einschaltdauer (40°C - 10 min)	30% 200A	30% 200A	\
			60% 150A	60% 150A	60% 160A
			100% 110A	100% 110A	100% 123A
No load voltage	Open spanning	Leerlaufspannung	54		
Efficiency	cos φ	cos φ	85		
Power factor	Rendement	Wirkungsgrad	0.76		
IP	IP	IP	21S		
Insulation class	Isolatieklasse	Schutzklasse	H		
Cooling way	Koeling	Kühlung	FAN & AIR		
Dimensions mm	Afmetingen mm	Masse Gerät mm	520X220X390		
Wire diameter Ø	Draad diameter Ø	Draht durchmesser Ø	0.6 - 0.8 - 1.0		2.5 - 3.2
Electrode type	Elektrode type	Elektrode Typ	6013, 7018, etc.		
Net weight Kg	Gewicht Kg	Gewicht Gerät Kg	12.5		

ROWAC