

ROWAC

CUT 40SK LCD / CUT 60 LCD



GB CUT-40SK LCD/60 LCD

- Cutting capacity increased 2 times higher in cutting speed compared with oxy-cutting
- Suitable metal sheet can be cut easily and quickly
- Suitable for cutting stainless steel, copper, iron and aluminium etc
- Simple operation and smooth cutting surface
- Non-touch arc-starting, less damage to the torch tips
- Supplied complete with plasma cutting torch and earth clamp, reducing valve and carton box

NL CUT-40SK LCD/60 LCD

- De snijcapaciteit is 2 maal hoger qua snijsnelheid vergeleken met autogeen snijden
- Geschikte metaalplaten kunnen eenvoudig en snel worden gesneden
- Geschikt voor het snijden van roestvrij staal, koper, ijzer en aluminium etc
- Eenvoudige bediening en glad snijoppervlak
- Boogstart zonder aanraking, minder schade aan de toortspunten
- Compleet geleverd met plasmasnijtoorts en aardklem, reduceerventiel en kartonnen doos

ROWAC CUT 40SK LCD / CUT 60 LCD



Type Parameters		CUT-40SK LED	CUT-60 LED
Input voltage (V)	Ingangsspanning (V)	AC220V±10%	400V±10%,3PH
Rated input capacity (KVA)	Nominaal ingangsvermogen (KVA)	6.8	7.5
Rate input current (A)	Tarief ingangsstroom (A)	31	11
No-load voltage (V)	Onbelaste spanning (V)	290	320
Current Range (A)	Stroombereik (A)	20-40	20-60
Rate output voltage (V)	Uitgangsspanning (V)	88-96	88-104
Duty cycle (40°C, 10min)	Inschakelduur (40°C, 10min)	30	30% 60A
			60% 42A
			100% 33A
Efficiency (%)	Rendement (%)	77	86
Power factor	Arbeidsfactor	0.73	0.99
Insulation Class	Isolatieklasse	H	H
Housing Protection Class	Beschermingsgraad behuizing	IP21S	IP21S
Arcing Way	vonkoverslag	NON Touch	NON Touch
Pressure of air compressor (MPa)	Druk van luchtcompressor (MPa)	0.3-0.45	0.3-0.6
Nozzle Inside Hole (mm)	Mondstuk binnengat (mm)	0.9	1.1
Max cutting thickness	Maximale snijdikte	1-25	40mm
Grid cutting	Raster snijden	YES	YES
Weight (kg)	Gewicht (kg)	7.3	13.2±0.2
Dimensions (mm)	Afmetingen (mm)	455x150x280	460X224X327

ROWAC